



6V、12V FMJ VRLA gel battery

Type	Rated Voltage (V)	Rated Capacity (Ah)			Dimension (mm)				Weight (kg)	
		10hr	3hr	1hr	Length	Width	High	Total Height		
		Final Voltage *10.80V	Final Voltage *10.80V	Final Voltage *10.50V						
6-FMJ-24	12	24	18	13.2	164	124	179	176	9.0	
6-FMJ-38		38	28.5	20.9	195	165	175	175	12.5	
6-FMJ-55		55	41.2	30.2	260	165	170	170	16.5	
6-FMJ-65		65	48.7	35.7	351	165	180	180	22.0	
6-FMJ-80		80	60	44	331	172	215	218	24.5	
6-FMJ-90		90	67.5	49.5	331	172	215	218	27.0	
6-FMJ-100		100	75	55	331	172	215	218	29.5	
6-FMJ-120		120	90	66	407	172	233	259	35.5	
6-FMJ-135		135	101.2	74.2	341	173	258	283	41.5	
6-FMJ-140		140	105	77	360	172	240	240	42.0	
6-FMJ-150		150	112.5	82.5	483	170	240	240	42.5	
6-FMJ-200		200	150	110	522	240	214	244	62.0	
3-FMJ-200		6	200	150	110	260	180	270	271	30.5
3-FMJ-260			260	195	143	341	180	270	273	42.0

OPzS series lead-acid stationary battery

Type	Rated Voltage (V)	Rated Capacity (Ah)			Dimension (mm)				Weight (kg)	
		10hr	1hr	0.5hr	Length	Width	High	Total Height		
		Final Voltage *1.80V	Final Voltage *1.75V	Final Voltage *1.65V						
4 OPzS 200	2	200	90	70	104	207	356	411	17.5	
5 OPzS 250		250	112.5	87.5	125				21.2	
6 OPzS 300		300	135	105	146				24.8	
5 OPzS 350		350	157.5	122.5	125				28.5	
6 OPzS 420		420	189	147	146				34.1	
7 OPzS 490		490	220.5	171.5	167				38.5	
6 OPzS 600		600	270	210	146	211	647	702	47.1	
8 OPzS 800		800	360	280	192				63.9	
10 OPzS 1000		1000	450	350	234				78.0	
12 OPzS 1200		1200	540	420	276				92.0	
12 OPzS 1500		1500	675	525	276	213	774	829	110.8	
16 OPzS 2000		2000	900	700	400				215	152.0
20 OPzS 2500		2500	1125	875	488				186.7	
24 OPzS 3000		3000	1350	1050	577				223.3	
28 OPzS 3500	3500	1575	1225	577	241.8					
6V 3 OPzS 150	6	150	67.5	52.5	273	207	353	389	41.0	
6V 4 OPzS 200		200	90	70	273				47.0	
6V 5 OPzS 250		250	112.5	87.5	381				61.0	
6V 6 OPzS 300		300	135	105	381				66.5	
12V 1 OPzS 50	12	50	22.5	17.5	273	207	353	389	38.0	
12V 2 OPzS 100		100	45	35	273				49.0	
12V 3 OPzS 150		150	67.5	52.5	381				68.0	